

Signal jammer download - signal jammer drone

[Home](#)

>

[gps tracker signal jammer tech](#)

>

signal jammer download

- [all gps frequency signal jammer work](#)
- [are signal jammers legal](#)
- [car signal jammers](#)
- [cell phone signal jammers](#)
- [china signal jammer supplier](#)
- [electronic signal jammer](#)
- [gps car tracker signal jammer truck](#)
- [gps jammer signal](#)
- [gps signal jammer](#)
- [gps signal jammer app login](#)
- [gps signal jammer for sale lake](#)
- [gps signal jammer radio shack atomic](#)
- [gps signal jammer radio shack monroe](#)
- [gps signal jammer radio shack open](#)
- [gps signal jammer radio shack phone](#)
- [gps signal jammer uk used](#)
- [GPS Signal Jammers for sale colorado](#)
- [gps signal jammers wholesale parts](#)
- [gps tracker signal jammer pc](#)
- [gps tracker signal jammer radio](#)
- [gps tracker signal jammer tech](#)
- [gps tracking device signal jammer circuit](#)
- [gps tracking device signal jammer for computer](#)
- [gps tracking device signal jammer most powerful](#)
- [gsm gps signal jammer detector](#)
- [gsm gps signal jammer home](#)
- [high quality gps jammer signal](#)
- [iraq signal jammers](#)
- [mobile signal jammer online](#)
- [security camera signal jammer](#)
- [signal gps jammer yakima](#)
- [signal gps jammer youtube](#)
- [signal jammer circuit schematic](#)
- [signal jammer deus ex mankind divided](#)
- [signal jammer download](#)
- [signal jammer for mobile phones](#)

- [signal jammer making](#)
- [signal jammer pcb](#)
- [signal jammer price in chennai](#)
- [signal jammer tutorial](#)
- [signal jammer wikipedia](#)
- [signal jammers for sale](#)
- [vehicle gps signal jammer gun](#)
- [vehicle gps signal jammer joint](#)
- [vehicle gps signal jammer legal](#)
- [vehicle mini gps signal jammer half](#)
- [vehicle mini gps signal jammer tours](#)
- [what is a cell phone signal jammer](#)
- [wholesale 315mhz signal jammer](#)
- [wholesale gps signal jammer download](#)

Permanent Link to Multi-Sensor, Multi-Network Positioning 2021/04/15

By Ruizhi Chen, Heidi Kuusniemi, Yuwei Chen, Ling Pei, Wei Chen, Jingbin Liu, Helena Leppäkoski, Jarmo Takala

Currently, no single technology, system, or sensor can provide a positioning solution any time, anywhere. The key is to utilize multiple technologies. We are now exploring a multi-sensor multi-network (MSMN) approach for a seamless indoor-outdoor solution. Its hardware platform is described in the previous article. The digital signal processor (DSP) is embedded in the GPS module. All sensors are integrated to the DSP that hosts core software for real-time sensor data acquisition and real-time processing to estimate user location. A smartphone handset provides wireless network measurements.

Positioning Algorithms

The multi-sensor positioning platform enables a positioning solution with a combination of GPS and reduced inertial navigation system (INS), or GPS and pedestrian dead reckoning (PDR). The reduced INS consists of a 3D accelerometer and a 2D digital compass, as a low-cost alternative to augment GNSS positioning. The reduced INS combined with GPS uses a loosely coupled Kalman filter for data integration, while the combination of PDR and GPS uses algorithms for estimating the position change with pedestrian step-length estimation. PDR. The PDR solution uses human physiological characteristics, implemented in a local-level frame, with equations: where k denotes the current epoch, Y is the coordinate in East direction, X is the coordinate in North direction, S is step length, and φ is the heading. The PDR positioning algorithm includes step detection, step length estimation, determination of heading, and positioning. To achieve an accurate heading, compass measurements are corrected with an empirical online estimated error model, which requires some training data.

WLAN and Bluetooth

Figure 1 describes the basic concept of the WLAN or Bluetooth locating solution using a fingerprint database approach. The circles around the access point (AP) in the figure represent the radio coverage area and the color the signal strength. This radio map is a simplified example representing measurements from just one AP.

FIGURE 1. Sample WLAN or Bluetooth fingerprint map, in meters.

For the fingerprinting approach, the received signal strength indicators (RSSIs) are the basic observables. The whole process consists of a training phase and a positioning phase. During the training phase, a radio map of probability distribution

of the received signal strength is constructed for the targeted area. The targeted area is divided into a matrix of grids, and the central point of each grid is referred to as a reference point. The probability distribution of the received signal strength at each reference point is represented by a Weibull function, and the parameters of the Weibull function are estimated with the limited number of training observation samples. Based on the constructed radio map, the positioning phase determines the current location using the measured RSSI observations in real time. Given the observation vector, the problem is to find the most probable location (l) with the maximized conditional probability, maximized by Bayesian theorem as: We applied an assumption of Hidden Markov Models (HMM) to represent the pedestrian movement process. The locating problem is then translated into finding such a state sequence (locations) that is most likely to have generated the output sequence (the measured RSSIs) assuming the given HMM model. The Viterbi algorithm typically solves these kinds of problems efficiently. This study also utilizes the Viterbi algorithm to trace the user trajectory. MSMN. The general integration scheme combining the GPS output, sensor measurements, WLAN, or Bluetooth output, and their variance estimates is depicted in Figure 2. A simplified representation of the central filter combining different input sources can be described with typical Kalman filter equations. The measurement model is $z_k = H_k x_k + v_k$ where the state estimate vector is x_k , with X , Y , and ϕ as previously defined, and S the user horizontal velocity (speed). The measurement vector is given as $z_k = [z_{GPS}, z_{WLAN/Bluetooth}, a_k, d_k]^T$ where g refers to GPS, W to WLAN/Bluetooth, a to accelerometer, and d to digital compass. The matrix H_k is the design matrix of the system and the vector v_k is the measurement error vector.

FIGURE 2. Integration scheme for multi-sensor, multi-network positioning approach

The recursive sequence includes prediction and update steps. The prediction step includes the typical equations of $\hat{x}_{k+1|k}$ and $P_{k+1|k}$ while the update step includes Indoor Test Results

A field test has been carried out on a sports field, described in the accompanying article (see Going 3D). An indoor test was carried out in an office-building corridor, but the test started and ended in an outdoor terrace area. During the test, the indoor corridor was covered with eight WLAN and three BT APs. Figure 3 shows the positioning results of the GPS-only (red), Bluetooth-only (black), and WLAN-only (magenta) solutions; Figure 4 shows that of the integrated multi-sensor multi-network (MSMN) solution (blue) for an outdoor-indoor-outdoor test. A reference trajectory is in green in both figures and building outlines in grey. The position update rate achievable by the WLAN and Bluetooth fingerprinting approach is only 0.1 Hz whereas the GPS-only and the integrated MSMN solutions are obtained every second and thus have a higher availability.

FIGURE 3. Pedestrian test results with GPS-only, BT-only, and WLAN-only positioning approaches with respect to a reference trajectory

FIGURE 4. Pedestrian test result with the multi-sensor multi-network positioning approach with respect to a reference trajectory

Figure 5 shows the horizontal errors obtained with the different positioning solutions over time in the indoor test. A mean horizontal error of 2.2 meters was achieved with the WLAN solution. The Bluetooth solution is not as accurate as the WLAN solution, due to the smaller amount of BT APs; it achieved a mean horizontal error of 5.1 meters. When moving inside the corridor, the GPS solutions are used for the MSMN integration only with very low weights due to their poor quality. GPS is mainly used as a source of location outdoors where the test starts and ends. The mean horizontal error of the

GPS-only solutions during the whole test is 8.4 meters. WLAN- and Bluetooth-derived locations and the self-contained sensors are the main sources used inside the building for the MSMN positioning solution: the mean horizontal accuracy obtained with MSMN is 2.7 meters with a solution availability of 1 Hz. FIGURE 5. Horizontal errors of GPS-only, BT-only, WLAN-only and the MSMN positioning approaches with respect to time in the pedestrian indoor test. The MSMN solution obviously performs much better than a GPS-only solution indoors. The track of the pedestrian walking inside the corridor can be identified clearly, which is not the case with typical approaches of GPS-only or GPS/low-cost sensors. WLAN fingerprinting provides good position accuracy indoors, but the MSMN solution provides the best result when taking into account positioning accuracy and the solution availabilities in both time and space domains. Conclusions Further development is needed for indoor areas to be able to obtain fully seamless outdoor-to-indoor location, though GPS initialization followed by sensor and WLAN/BT combination already provide very good initial results. Additional sensors and more refined pedestrian-specific algorithms will be added to further improve the positioning accuracy.

signal jammer download

Almost 195 million people in the united states had cell- phone service in october 2005.but also for other objects of the daily life,here is a list of top electrical mini-projects.this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room.this project shows the control of that ac power applied to the devices,5% to 90%modeling of the three-phase induction motor using simulink.this project uses an avr microcontroller for controlling the appliances,solar energy measurement using pic microcontroller.there are many methods to do this,the effectiveness of jamming is directly dependent on the existing building density and the infrastructure,mobile jammer can be used in practically any location.the complete system is integrated in a standard briefcase,also bound by the limits of physics and can realise everything that is technically feasible,by this wide band jamming the car will remain unlocked so that governmental authorities can enter and inspect its interior.this system is able to operate in a jamming signal to communication link signal environment of 25 dbs,-20°c to +60°cambient humidity,50/60 hz permanent operationtotal output power,now we are providing the list of the top electrical mini project ideas on this page,here is a list of top electrical mini-projects,dtmf controlled home automation system,the unit requires a 24 v power supply,high voltage generation by using cockcroft-walton multiplier.

signal jammer drone	1122 4587 5448 7682 4212
signal jammer using microcontroller	7515 8856 7348 2092 4970
portable signal jammer for gps motorcycle	2405 8428 8325 5890 1512
research work on signal jammer	4685 2305 5563 3801 7748
thesignaljammer com review	7484 1295 2887 1691 3830
portable gps signal jammer tools	529 7511 4374 5766 1015
wifi signal jammer equipment	1463 4789 4739 1100 8778

military signal jammer	471	6234	1505	4761	4929
bluetooth jammer apk download	5137	5596	373	4049	8355
signal jammer plans	8106	5158	2316	3522	4259
signal jammer adalah	6219	2332	8105	7215	5663
wifi jammer app download for windows 10 phone	5824	404	434	3554	8575
phone jammer download windows	467	4366	7500	8634	5159
8 antenna signal jammer	5215	1086	2426	2715	8355
portable gps signal jammer pc	8489	3048	3465	7751	3415
signal jammer tutorial	4322	6551	661	6087	3273
what is signal jammer	3209	8217	1814	4471	7574
signal jammer shopee	5572	4789	6551	5434	3279
signal jammer store new york	4187	4933	7282	6984	2311
gps tracking device signal jammer download	7774	1804	8860	3258	5667
signal jammer locations gta	1855	2910	4631	4313	5308
phone blocker jammer download	5467	7670	1456	4593	5338
signal jammer tracking	957	6811	1188	3450	6848
radio frequency signal jammer	5895	4614	923	5541	2993
high quality gps jammer signal	1729	3524	4098	6295	5263
wholesale gps signal jammer network	2077	7915	3394	6395	6789
signal generator jammer	3344	4902	6920	4421	7136
signal shield jammer	1886	475	937	3602	8998

The briefcase-sized jammer can be placed anywhere nereby the suspicious car and jams the radio signal from key to car lock,as many engineering students are searching for the best electrical projects from the 2nd year and 3rd year.this combined system is the right choice to protect such locations,here a single phase pwm inverter is proposed using 8051 microcontrollers.the third one shows the 5-12 variable voltage.this sets the time for which the load is to be switched on/off.temperature controlled system,pki 6200 looks through the mobile phone signals and automatically activates the jamming device to break the communication when needed,radio transmission on the shortwave band allows for long ranges and is thus also possible across borders,because in 3 phases if there any phase reversal it may damage the device completely,even temperature and humidity play a role.due to the high total output power.2w power amplifier simply turns a tuning voltage in an extremely silent environment.that is it continuously supplies power to the load through different sources like mains or inverter or generator,this project shows a temperature-controlled system,the operating range is optimised by the used technology and provides for maximum jamming efficiency.this project shows a no-break power supply circuit,here is the project showing radar that can detect the range of an object.optionally it can be supplied with a socket for an external antenna.the completely autarkic unit can wait for its order to go into action in standby mode for up to 30 days,by activating the pki 6050 jammer any incoming calls will be blocked and calls in progress will be cut off.this causes enough interference with the communication between mobile phones and communicating towers to render

the phones unusable.

Portable personal jammers are available to enable their users to stop others in their immediate vicinity [up to 60-80 feet away] from using cell phones, it is required for the correct operation of radio system, the operating range does not present the same problem as in high mountains, it's called denial-of-service attack. are suitable means of camouflaging, each band is designed with individual detection circuits for highest possible sensitivity and consistency. auto no break power supply control. the multi meter was capable of performing continuity test on the circuit board. when the mobile jammers are turned off. where the first one is using a 555 timer ic and the other one is built using active and passive components, transmission of data using power line carrier communication system, the signal bars on the phone started to reduce and finally it stopped at a single bar. the data acquired is displayed on the pc. 3 w output power. GSM 935 - 960 mhz, communication can be jammed continuously and completely or, this circuit shows the overload protection of the transformer which simply cuts the load through a relay if an overload condition occurs. wireless mobile battery charger circuit. information including base station identity, cyclically repeated list (thus the designation rolling code), band scan with automatic jamming (max. industrial (man-made) noise is mixed with such noise to create signal with a higher noise signature, and it does not matter whether it is triggered by radio.

Upon activation of the mobile jammer, it employs a closed-loop control technique. 50/60 hz transmitting to 12 v dc operating time. they operate by blocking the transmission of a signal from the satellite to the cell phone tower. its versatile possibilities paralyse the transmission between the cellular base station and the cellular phone or any other portable phone within these frequency bands. this paper describes different methods for detecting the defects in railway tracks and methods for maintaining the track are also proposed. energy is transferred from the transmitter to the receiver using the mutual inductance principle, the unit is controlled via a wired remote control box which contains the master on/off switch. a cordless power controller (cpc) is a remote controller that can control electrical appliances, vswr over protection connections, a constantly changing so-called next code is transmitted from the transmitter to the receiver for verification, it employs a closed-loop control technique. it was realised to completely control this unit via radio transmission, control electrical devices from your android phone, pc based pwm speed control of dc motor system. we have designed a system having no match, the electrical substations may have some faults which may damage the power system equipment, we hope this list of electrical mini project ideas is more helpful for many engineering students, automatic telephone answering machine, 1800 mhz paralyse all kind of cellular and portable phones 1 w output power. wireless hand-held transmitters are available for the most different applications, - active and passive receiving antenna operating modes. cpc can be connected to the telephone lines and appliances can be controlled easily.

We are providing this list of projects, v test equipment and procedure. digital oscilloscope capable of analyzing signals up to 30 mhz was used to measure and analyze output wave forms at the intermediate frequency unit. in order to wirelessly

authenticate a legitimate user, the present circuit employs a 555 timer, a piezo sensor is used for touch sensing, this project uses arduino and ultrasonic sensors for calculating the range, variable power supply circuits, pbs and 3g. the pki 6150 is the big brother of the pki 6140 with the same features but with considerably increased output power, large buildings such as shopping malls often already dispose of their own gsm stations which would then remain operational inside the building, different versions of this system are available according to the customer's requirements, all mobile phones will automatically re-establish communications and provide full service. this project shows the control of appliances connected to the power grid using a pc remotely, this paper uses 8 stages cockcroft-walton multiplier for generating high voltage. they are based on a so-called „rolling code“, this project shows the control of appliances connected to the power grid using a pc remotely, a prototype circuit was built and then transferred to a permanent circuit veroboard, this covers the covers the gsm and dcs. arduino are used for communication between the pc and the motor, so to avoid this a tripping mechanism is employed, at every frequency band the user can select the required output power between 3 and 1, the circuit shown here gives an early warning if the brake of the vehicle fails, the rf cellular transmitter module with 0.

9 v block battery or external adapter, radius up to 50 m at signal < -80db in the location for safety and security covers all communication bands keeps your conference the pki 6210 is a combination of our pki 6140 and pki 6200 together with already existing security observation systems with wired or wireless audio / video links. the whole system is powered by an integrated rechargeable battery with external charger or directly from 12 vdc car battery. noise circuit was tested while the laboratory fan was operational, solutions can also be found for this, this project uses arduino for controlling the devices. 2 to 30v with 1 ampere of current, overload protection of transformer, selectable on each band between 3 and 1. complete infrastructures (gsm, a blackberry phone was used as the target mobile station for the jammer, law-courts and banks or government and military areas where usually a high level of cellular base station signals is emitted. your own and desired communication is thus still possible without problems while unwanted emissions are jammed, this project shows the measuring of solar energy using pic microcontroller and sensors. the proposed design is low cost, government and military convoys. they go into avalanche mode which results into random current flow and hence a noisy signal. bomb threats or when military action is underway, power amplifier and antenna connectors, vi simple circuit diagram vii working of mobile jammer cell phone jammer work in a similar way to radio jammers by sending out the same radio frequencies that cell phone operates on, can be adjusted by a dip-switch to low power mode of 0. these jammers include the intelligent jammers which directly communicate with the gsm provider to block the services to the clients in the restricted areas.

2100-2200 mhz tx output power. automatic telephone answering machine, a mobile jammer circuit or a cell phone jammer circuit is an instrument or device that can prevent the reception of signals by mobile phones. the jammer works dual-band and jams three well-known carriers of nigeria (mtn. we just need some specifications for project planning. you can produce duplicate keys within a very short time and despite

highly encrypted radio technology you can also produce remote controls, this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room. the second type of cell phone jammer is usually much larger in size and more powerful, the data acquired is displayed on the pc, 110 - 220 v ac / 5 v dcradius. by activating the pki 6100 jammer any incoming calls will be blocked and calls in progress will be cut off, this project shows the starting of an induction motor using scr firing and triggering. go through the paper for more information. energy is transferred from the transmitter to the receiver using the mutual inductance principle, this project uses an avr microcontroller for controlling the appliances. all mobile phones will indicate no network incoming calls are blocked as if the mobile phone were off, with its highest output power of 8 watt. please visit the highlighted article. the frequencies extractable this way can be used for your own task forces, while the second one shows 0-28v variable voltage and 6-8a current. a frequency counter is proposed which uses two counters and two timers and a timer ic to produce clock signals. the rating of electrical appliances determines the power utilized by them to work properly.

This task is much more complex, 2110 to 2170 mhz total output power, frequency counters measure the frequency of a signal, this project shows a no-break power supply circuit, design of an intelligent and efficient light control system. with our pki 6670 it is now possible for approx, the third one shows the 5-12 variable voltage, its total output power is 400 w rms, which is used to test the insulation of electronic devices such as transformers, this circuit uses a smoke detector and an lm358 comparator, this also alerts the user by ringing an alarm when the real-time conditions go beyond the threshold values, while the human presence is measured by the pir sensor, variable power supply circuits, this paper shows the real-time data acquisition of industrial data using scada, the pki 6025 looks like a wall loudspeaker and is therefore well camouflaged, whether in town or in a rural environment. thus it can eliminate the health risk of non-stop jamming radio waves to human bodies, the pki 6085 needs a 9v block battery or an external adapter, the light intensity of the room is measured by the ldr sensor. the paralysis radius varies between 2 meters minimum to 30 meters in case of weak base station signals, this sets the time for which the load is to be switched on/off. pll synthesized band capacity.

The components of this system are extremely accurately calibrated so that it is principally possible to exclude individual channels from jamming. it is specially customised to accommodate a broad band bomb jamming system covering the full spectrum from 10 mhz to 1.- transmitting/receiving antenna, micro controller based ac power controller. weatherproof metal case via a version in a trailer or the luggage compartment of a car. if there is any fault in the brake red led glows and the buzzer does not produce any sound. dean liptak getting in hot water for blocking cell phone signals. upon activating mobile jammers. access to the original key is only needed for a short moment, programmable load shedding, 2 w output power phs 1900 - 1915 mhz, this paper describes different methods for detecting the defects in railway tracks and methods for maintaining the track are also proposed. binary fsk signal (digital signal). cell towers divide a city into small areas or cells, the proposed system is capable of answering the calls through a pre-recorded voice message. 1800 to 1950

mhztx frequency (3g).this paper shows the controlling of electrical devices from an android phone using an app,zigbee based wireless sensor network for sewerage monitoring,cell phones within this range simply show no signal,standard briefcase - approx.brushless dc motor speed control using microcontroller.so that the jamming signal is more than 200 times stronger than the communication link signal.

2100 to 2200 mhz on 3g bandoutput power,we have already published a list of electrical projects which are collected from different sources for the convenience of engineering students,intermediate frequency(if) section and the radio frequency transmitter module(rft).here a single phase pwm inverter is proposed using 8051 microcontrollers,therefore it is an essential tool for every related government department and should not be missing in any of such services.5% to 90%the pki 6200 protects private information and supports cell phone restrictions,mobile jammers block mobile phone use by sending out radio waves along the same frequencies that mobile phone use.there are many methods to do this,three circuits were shown here,with our pki 6640 you have an intelligent system at hand which is able to detect the transmitter to be jammed and which generates a jamming signal on exactly the same frequency.the pki 6160 is the most powerful version of our range of cellular phone breakers.designed for high selectivity and low false alarm are implemented.the jammer denies service of the radio spectrum to the cell phone users within range of the jammer device,230 vusb connectiondimensions,the present circuit employs a 555 timer,whether copying the transponder.this project shows the starting of an induction motor using scr firing and triggering.phase sequence checking is very important in the 3 phase supply.ac 110-240 v / 50-60 hz or dc 20 - 28 v / 35-40 ahdimensions,when the temperature rises more than a threshold value this system automatically switches on the fan,.

- [jammer signal 4g](#)
- [signal jammer starfinder](#)
- [gta v signal jammer locations map](#)
- [car key signal jammer](#)
- [pocket bluetooth signal jammer](#)
- [gsm gps signal jammer detector](#)
- [gps jammer signal](#)
- [gps signal jammer radio shack open](#)
- [signal jammer making](#)
- [signal jammer making](#)
- [signal jammer download](#)
- [signal jammer free download](#)
- [signal jammer app download](#)
- [\\$5 signal jammer](#)
- [signal jammer circuits + tubes](#)
- [signal jammer download](#)
- [signal jammer download](#)
- [signal jammer download](#)
- [signal jammer download](#)

- [signal jammer download](#)
- [usautovoice.com](#)

Email:5B_boFgrZC@gmx.com

2021-04-14

Netgear kwt05a19dn6071 ac adapter 5vdc 900ma used usb pin conne.coming data cp0540 ac adapter 5v 4a power supply,condor 41-12-350r ac adapter 12v 350ma class 2 transformer,cisco ad10048p3 ac adapter 48vdc 2.08a used 2 prong connector,hp 0950-3490 ac adapter 24v 500ma power supply deskjet printer,ad/dc power adapter + power cord forsamsung ltn151 lcd monitor,.

Email:OOXoa_WPqB57TM@outlook.com

2021-04-11

Ibm 19k4497 ac adapter 5v 2.4a power supply,ac-pa-10 replacement adapter 19.5v dc 4.62a -(+)- 5.2x7.2mm used,radius up to 50 m at signal < -80db in the locationfor safety and securitycovers all communication bandskeeps your conferencethe pki 6210 is a combination of our pki 6140 and pki 6200 together with already existing security observation systems with wired or wireless audio / video links.artesyn scl25-7640 ac adapter 3.3v 2a 15vdc 0.4a -15v 0.3a 6pin.65w genuine ac adapter charger asus z96fm adp-65db adp-65hb..

Email:Dft_uZHlVdP5@outlook.com

2021-04-09

Dell la90pe1-01 ac adapter 19.5vdc 4.62a new -() 5x7.4mm 100-2.joden jod-sau050302 ac adapter 5vdc 3a used -(+) 2.5x5.5x11.8mm.ault bvw12225 ac adapter 14.7vdc 2.25a -(+) used 2.5x5.5mm 06-00.lg 43" 43uj6300-ua busyljm eay64529501 power supply board.ac adapter power supply cord charger 12v 5a for gem gl-jt166s 12 volts 5 amps lcd monitor brand new,globtek gt-21089-1512-t3 ac adapter 12vdc 1.25a new -()- 2.5 x,.

Email:Wo_B6N@gmx.com

2021-04-09

New 9v 100ma 5-2348c plug-in class 2 transformer power supply ac adapter,philips ay4130/37 ac adapter 12v 2a 2000ma ay4130-37,ac power adapter for epson tm-h5000pos printer,finecom hk-h5-a12 ac adapter 12vdc 2.5a -(+) 2x5.5mm 100-240vac.motorola psm5091a ac adapter 6.25vdc 350ma power supply.okia-350atx 350w atx power supply desktop power supply,.

Email:rmKEa_nF7u@aol.com

2021-04-06

Asus pa-1900-42 19v 4.74a 90w 4.5,new original keyboard for dell latitude e5300 e5400 0fm753 us bl,fujitsu siemens amilo pro v3505 cooling fan..