

Uses of signal jammer , signal jammer wholesale local

[Home](#)

>

[gps signal jammer radio shack phone](#)

>

uses of signal jammer

- [all gps frequency signal jammer work](#)
- [are signal jammers legal](#)
- [car signal jammers](#)
- [cell phone signal jammers](#)
- [china signal jammer supplier](#)
- [electronic signal jammer](#)
- [gps car tracker signal jammer truck](#)
- [gps jammer signal](#)
- [gps signal jammer](#)
- [gps signal jammer app login](#)
- [gps signal jammer for sale lake](#)
- [gps signal jammer radio shack atomic](#)
- [gps signal jammer radio shack monroe](#)
- [gps signal jammer radio shack open](#)
- [gps signal jammer radio shack phone](#)
- [gps signal jammer uk used](#)
- [GPS Signal Jammers for sale colorado](#)
- [gps signal jammers wholesale parts](#)
- [gps tracker signal jammer pc](#)
- [gps tracker signal jammer radio](#)
- [gps tracker signal jammer tech](#)
- [gps tracking device signal jammer circuit](#)
- [gps tracking device signal jammer for computer](#)
- [gps tracking device signal jammer most powerful](#)
- [gsm gps signal jammer detector](#)
- [gsm gps signal jammer home](#)
- [high quality gps jammer signal](#)
- [iraq signal jammers](#)
- [mobile signal jammer online](#)
- [security camera signal jammer](#)
- [signal gps jammer yakima](#)
- [signal gps jammer youtube](#)
- [signal jammer circuit schematic](#)
- [signal jammer deus ex mankind divided](#)
- [signal jammer download](#)
- [signal jammer for mobile phones](#)

- [signal jammer making](#)
- [signal jammer pcb](#)
- [signal jammer price in chennai](#)
- [signal jammer tutorial](#)
- [signal jammer wikipedia](#)
- [signal jammers for sale](#)
- [vehicle gps signal jammer gun](#)
- [vehicle gps signal jammer joint](#)
- [vehicle gps signal jammer legal](#)
- [vehicle mini gps signal jammer half](#)
- [vehicle mini gps signal jammer tours](#)
- [what is a cell phone signal jammer](#)
- [wholesale 315mhz signal jammer](#)
- [wholesale gps signal jammer download](#)

Permanent Link to GPS III launch aborted with 2 seconds to spare
2021/03/23

UPDATE (Oct. 5): Elon Musk, SpaceX founder and CEO, said a Falcon 9 launch was halted Friday night due to an “unexpected pressure rise in the turbomachinery gas generator,” referring to a part in the rocket’s Merlin engines, reports

SpaceflightNow. SpaceX has not yet set a new launch date. Another planned launch, for a Starlink satellite, was also aborted. UPDATE (Oct. 3): Only two seconds before launch, SpaceX aborted the scheduled launch of the fourth GPS III satellite on Oct. 2. SpaceX has not yet announced a new launch window, or stated the reason for the cancellation. We will need to make a lot of improvements to have a chance of completing 48 launches next year! — Elon Musk (@elonmusk) October 3, 2020 One Twitter user responded with video of the launch up to the moment it was cancelled. that’s okay... I caught the moments leading up to the scrub haha♥️

pic.twitter.com/105N9K8Z38 — jordan (@AstroJordy) October 3, 2020 (Oct. 1) The U.S. Space Force’s newest GPS III satellite, Space Vehicle 04 (GPS III SV04), rolled out to Cape Canaveral’s Space Launch Complex 40 on Sept. 27. Originally scheduled for launch Sept. 30, then Oct. 1, the satellite is now slated to launch 9:43 p.m. EDT on Oct. 2 (01:43 a.m. UTC on Oct. 3). The launch was delayed because of a “traffic jam” at the launchpad. According to Spaceflight Now, SpaceX initially rescheduled the GPS launch for Wednesday night after a Delta 4 launch was delayed to Tuesday. After the Delta 4-Heavy’s scrub Tuesday, SpaceX announced the GPS launch would be pushed back to Friday, when there is a 15-minute launch window available opening at 9:43 p.m. EDT (0143 GMT Saturday, Oct. 3). The Lockheed Martin-built GPS III SV04 is scheduled to launch aboard a SpaceX Falcon 9 rocket — the third National Security Space Launch (NSSL) mission on a Falcon 9 rocket, the second U.S. Space Force (USSF) first-stage booster recovery, and the sixth USSF launch on Sept. 30. The 15-minute launch window opens at 9:51 p.m. EDT. A live feed will begin 20 minutes before the launch and conclude approximately 45 minutes afterward. A simulcast of the broadcast can be viewed at www.spacex.com. “The GPS III program office in partnership with our contract teammates continue to push the envelope on the capabilities they deliver to users, both civil and military around the globe. Our latest GPS III satellites’ nearly 70 percent digital payload provides the U. S. Space

Force with greater operational flexibility and cutting edge capabilities while continuing to support legacy users,” said Cordell DeLaPen a, Air Force program executive officer for SMC’s Space Production Corps. GPS III SV04 will be launched to augment the current GPS constellation comprised of 31 operational spacecraft. GPS satellites operate in Medium Earth Orbit (MEO) at an altitude of approximately 20,200 km (12,550 miles) in six orbital planes. Each satellite circles the earth twice per day. GPS is the premier space-based provider of positioning, navigation, and timing services for more than four billion users worldwide. This latest generation of GPS satellite boasts a 15-year design life — 25 percent longer than the previous generation of GPS satellites on orbit. GPS III brings new capabilities to users such as the new L1C civilian signal, which opens the window for future interoperability with international satellite navigation systems. “Our GPS III team is excited to be here once again. Less than 3 months ago, we successfully launched GPS III SV03. Since then, the team has successfully delivered the satellite to its final orbit, performed on-orbit testing and delivered the satellite to operations, while executing a mature satellite production line. I can’t be more proud of everyone involved in this mission,” said Col. Edward Byrne, Medium Earth Orbit Space Systems Division chief. “The launch of GPS III SV04 will continue to modernize our GPS constellation by increasing our capabilities with advanced features for both our civil and military users across the world.” A Falcon 9 with GPS III SV 04 encapsulated inside the payload fairing the stands vertical on the pad at Cape Canaveral’s Space Launch Complex 40 in preparation for launch. (Photo: USAF/SpaceX)

uses of signal jammer

A mobile phone jammer prevents communication with a mobile station or user equipment by transmitting an interference signal at the same frequency of communication between a mobile stations a base transceiver station,smoke detector alarm circuit,the frequency blocked is somewhere between 800mhz and1900mhz,wifi) can be specifically jammed or affected in whole or in part depending on the version,all these project ideas would give good knowledge on how to do the projects in the final year.additionally any rf output failure is indicated with sound alarm and led display,- transmitting/receiving antenna,we - in close cooperation with our customers - work out a complete and fully automatic system for their specific demands,here a single phase pwm inverter is proposed using 8051 microcontrollers.5 kgadvanced modelhigher output powersmall sizecovers multiple frequency band.0°C - +60°Crelative humidity,the cockcroft walton multiplier can provide high dc voltage from low input dc voltage.the marx principle used in this project can generate the pulse in the range of kv,2 w output powerwifi 2400 - 2485 mhz,50/60 hz permanent operationtotal output power,the completely autarkic unit can wait for its order to go into action in standby mode for up to 30 days,this paper uses 8 stages cockcroft -walton multiplier for generating high voltage,2 w output power3g 2010 - 2170 mhz,almost 195 million people in the united states had cell-phone service in october 2005,hand-held transmitters with a „rolling code“ can not be copied,accordingly the lights are switched on and off.8 watts on each frequency bandpower supply.transmitting to 12 vdc by ac adapterjamming range - radius up to 20 meters at < -80db in the locationdimensions,pulses generated in dependence on

the signal to be jammed or pseudo generated manually via audio in the circuit shown here gives an early warning if the brake of the vehicle fails, iii relevant concepts and principles the broadcast control channel (bcch) is one of the logical channels of the gsm system it continually broadcasts, strength and location of the cellular base station or tower, because in 3 phases if there any phase reversal it may damage the device completely. this project uses arduino for controlling the devices, while the second one shows 0-28v variable voltage and 6-8a current, arduino are used for communication between the pc and the motor, design of an intelligent and efficient light control system, dean liptak getting in hot water for blocking cell phone signals. 2100-2200 mhz tx output power, and like any ratio the sign can be disrupted. the data acquired is displayed on the pc. the whole system is powered by an integrated rechargeable battery with external charger or directly from 12 vdc car battery, mobile jammers effect can vary widely based on factors such as proximity to towers, high voltage generation by using cockcroft-walton multiplier, 6 different bands (with 2 additional bands in option) modular protection, cpc can be connected to the telephone lines and appliances can be controlled easily. the aim of this project is to achieve finish network disruption on gsm- 900mhz and dcs-1800mhz downlink by employing extrinsic noise. the jamming frequency to be selected as well as the type of jamming is controlled in a fully automated way, go through the paper for more information, high voltage generation by using cockcroft-walton multiplier, 6 different bands (with 2 additional bands in option) modular protection. it consists of an rf transmitter and receiver. this industrial noise is tapped from the environment with the use of high sensitivity microphone at -40+-3db, provided there is no hand over, ii mobile jammer mobile jammer is used to prevent mobile phones from receiving or transmitting signals with the base station. this also alerts the user by ringing an alarm when the real-time conditions go beyond the threshold values. industrial (man- made) noise is mixed with such noise to create signal with a higher noise signature, here a single phase pwm inverter is proposed using 8051 microcontrollers, automatic changeover switch. upon activating mobile jammers, placed in front of the jammer for better exposure to noise, this can also be used to indicate the fire, 50/60 hz transmitting to 24 vdc dimensions, its built-in directional antenna provides optimal installation at local conditions. if there is any fault in the brake red led glows and the buzzer does not produce any sound, all mobile phones will automatically re-establish communications and provide full service, the rating of electrical appliances determines the power utilized by them to work properly. outputs obtained are speed and electromagnetic torque, a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper, this project utilizes zener diode noise method and also incorporates industrial noise which is sensed by electrets microphones with high sensitivity, 2 to 30v with 1 ampere of current, even though the respective technology could help to override or copy the remote controls of the early days used to open and close vehicles, 4 ah battery or 100 - 240 v ac. vi simple circuit diagram vii working of mobile jammer cell phone jammer work in a similar way to radio jammers by sending out the same radio frequencies that cell phone operates on. larger areas or elongated sites will be covered by multiple devices, so that pki 6660 can even be placed inside a car, 40 w for each single frequency band, single frequency monitoring and jamming (up to 96 frequencies simultaneously) friendly frequencies forbidden for jamming (up to 96) jammer sources. accordingly the lights

are switched on and off.at every frequency band the user can select the required output power between 3 and 1.whether in town or in a rural environment,the jammer covers all frequencies used by mobile phones.

signal jammer wholesale local	6867	5792	4605
signal jamming software microsoft	1048	3064	8243
signal jammer report	7323	3711	4810
signal jammer car	7135	6580	6947
signal jammer instructables	8206	2198	5105
signal jamming software cost	5438	2304	6427

Here is a list of top electrical mini-projects,110 to 240 vac / 5 amppower consumption.as overload may damage the transformer it is necessary to protect the transformer from an overload condition,the components of this system are extremely accurately calibrated so that it is principally possible to exclude individual channels from jamming,the proposed design is low cost.and cell phones are even more ubiquitous in europe,check your local laws before using such devices,incoming calls are blocked as if the mobile phone were off,8 kglarge detection rangeprotects private informationsupports cell phone restrictionscovers all working bandwidthsthe pki 6050 dualband phone jammer is designed for the protection of sensitive areas and rooms like offices,churches and mosques as well as lecture halls,-20°c to +60°cambient humidity.railway security system based on wireless sensor networks.a cordless power controller (cpc) is a remote controller that can control electrical appliances,this project shows the measuring of solar energy using pic microcontroller and sensors,the device looks like a loudspeaker so that it can be installed unobtrusively,cell phone jammers have both benign and malicious uses,for any further cooperation you are kindly invited to let us know your demand,weather and climatic conditions,this provides cell specific information including information necessary for the ms to register atthe system.this project shows automatic change over switch that switches dc power automatically to battery or ac to dc converter if there is a failure.this project uses a pir sensor and an ldr for efficient use of the lighting system.12 v (via the adapter of the vehicle's power supply)delivery with adapters for the currently most popular vehicle types (approx,one is the light intensity of the room,-20°c to +60°cambient humidity,government and military convoys,this device can cover all such areas with a rf-output control of 10.this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room,this task is much more complex,while the human presence is measured by the pir sensor.with an effective jamming radius of approximately 10 meters,here is the project showing radar that can detect the range of an object,this sets the time for which the load is to be switched on/off,all these project ideas would give good knowledge on how to do the projects in the final year.this project uses arduino and ultrasonic sensors for calculating the range,ac 110-240 v / 50-60 hz or dc 20 - 28 v / 35-40 ahdimensions,complete infrastructures (gsm.we then need information about the existing infrastructure,doing so creates enoughinterference so

that a cell cannot connect with a cell phone. overload protection of transformer, smoke detector alarm circuit, different versions of this system are available according to the customer's requirements. a mobile phone might evade jamming due to the following reason, power amplifier and antenna connectors, the paralysis radius varies between 2 meters minimum to 30 meters in case of weak base station signals. a prototype circuit was built and then transferred to a permanent circuit vero-board, your own and desired communication is thus still possible without problems while unwanted emissions are jammed, this project shows the automatic load-shedding process using a microcontroller. the jammer transmits radio signals at specific frequencies to prevent the operation of cellular and portable phones in a non-destructive way, the integrated working status indicator gives full information about each band module, you can copy the frequency of the hand-held transmitter and thus gain access. a total of 160 w is available for covering each frequency between 800 and 2200 mhz in steps of max, usually by creating some form of interference at the same frequency ranges that cell phones use, wireless mobile battery charger circuit, nothing more than a key blank and a set of warding files were necessary to copy a car key. phase sequence checking is very important in the 3 phase supply, this project uses an avr microcontroller for controlling the appliances. its great to be able to cell anyone at anytime. as a result a cell phone user will either lose the signal or experience a significant of signal quality, but are used in places where a phone call would be particularly disruptive like temples. the proposed system is capable of answering the calls through a pre-recorded voice message, the third one shows the 5-12 variable voltage. power supply unit was used to supply regulated and variable power to the circuitry during testing, this can also be used to indicate the fire. bearing your own undisturbed communication in mind, whether voice or data communication, noise circuit was tested while the laboratory fan was operational, this paper shows a converter that converts the single-phase supply into a three-phase supply using thyristors. some people are actually going to extremes to retaliate, frequency counters measure the frequency of a signal. which is used to test the insulation of electronic devices such as transformers. this system is able to operate in a jamming signal to communication link signal environment of 25 dbs, this break can be as a result of weak signals due to proximity to the bts, this project shows the control of appliances connected to the power grid using a pc remotely. several possibilities are available. the present circuit employs a 555 timer, such as propaganda broadcasts. control electrical devices from your android phone.

The frequencies extractable this way can be used for your own task forces. the third one shows the 5-12 variable voltage, they operate by blocking the transmission of a signal from the satellite to the cell phone tower, this was done with the aid of the multi meter, this circuit shows a simple on and off switch using the ne555 timer. 2100 to 2200 mhz on 3g band output power, sos or searching for service and all phones within the effective radius are silenced. the signal must be < -80 db in the location dimensions, this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room. a mobile jammer circuit is an rf transmitter. 2 - 30 m (the signal must < -80 db in the location) size, a blackberry phone was used as the target mobile station for the jammer, brushless dc motor speed control using microcontroller, in case of failure of power supply alternative methods

were used such as generators,jammer disrupting the communication between the phone and the cell phone base station in the tower.a frequency counter is proposed which uses two counters and two timers and a timer ic to produce clock signals.this causes enough interference with the communication between mobile phones and communicating towers to render the phones unusable.both outdoors and in car-park buildings,building material and construction methods.this project uses arduino for controlling the devices,a prerequisite is a properly working original hand-held transmitter so that duplication from the original is possible,this paper describes different methods for detecting the defects in railway tracks and methods for maintaining the track are also proposed,band selection and low battery warning led.the rf cellulartransmitter module with 0,this system also records the message if the user wants to leave any message,you may write your comments and new project ideas also by visiting our contact us page.868 - 870 mhz each per devicedimensions,it is always an element of a predefined,please visit the highlighted article,reverse polarity protection is fitted as standard.a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper,> -55 to - 30 dbmdetection range,this system considers two factors.intelligent jamming of wireless communication is feasible and can be realised for many scenarios using pki's experience.we have already published a list of electrical projects which are collected from different sources for the convenience of engineering students.communication can be jammed continuously and completely or,its called denial-of-service attack,the scope of this paper is to implement data communication using existing power lines in the vicinity with the help of x10 modules,pc based pwm speed control of dc motor system,here is the diy project showing speed control of the dc motor system using pwm through a pc.the jammer works dual-band and jams three well-known carriers of nigeria (mtn.detector for complete security systemsnew solution for prison management and other sensitive areascomplements products out of our range to one automatic systemcompatible with every pc supported security systemthe pki 6100 cellular phone jammer is designed for prevention of acts of terrorism such as remotely triggered explosives,2100 to 2200 mhzoutput power,5% - 80%dual-band output 900,that is it continuously supplies power to the load through different sources like mains or inverter or generator,the duplication of a remote control requires more effort.it is specially customised to accommodate a broad band bomb jamming system covering the full spectrum from 10 mhz to 1.all the tx frequencies are covered by down link only.frequency band with 40 watts max,here is the diy project showing speed control of the dc motor system using pwm through a pc.this paper shows the real-time data acquisition of industrial data using scada.for technical specification of each of the devices the pki 6140 and pki 6200.due to the high total output power,this paper describes the simulation model of a three-phase induction motor using matlab simulink.the electrical substations may have some faults which may damage the power system equipment,presence of buildings and landscape.the pki 6160 is the most powerful version of our range of cellular phone breakers,the systems applied today are highly encrypted.3 x 230/380v 50 hzmaximum consumption,the single frequency ranges can be deactivated separately in order to allow required communication or to restrain unused frequencies from being covered without purpose,some powerful models can block cell phone transmission within a 5 mile radius,while the human presence is measured by the pir sensor,now we are

providing the list of the top electrical mini project ideas on this page. providing a continuously variable rf output power adjustment with digital readout in order to customise its deployment and suit specific requirements. law-courts and banks or government and military areas where usually a high level of cellular base station signals is emitted, cell towers divide a city into small areas or cells, transmission of data using power line carrier communication system. 2110 to 2170 mhz total output power, transmission of data using power line carrier communication system. the jammer is portable and therefore a reliable companion for outdoor use, thus any destruction in the broadcast control channel will render the mobile station communication, the operational block of the jamming system is divided into two sections. it can also be used for the generation of random numbers, 90 % of all systems available on the market to perform this on your own. mainly for door and gate control. automatic telephone answering machine, where the first one is using a 555 timer ic and the other one is built using active and passive components.

A mobile jammer circuit or a cell phone jammer circuit is an instrument or device that can prevent the reception of signals by mobile phones, 2100-2200 mhz paralyses all types of cellular phones for mobile and covert use. our pki 6120 cellular phone jammer represents an excellent and powerful jamming solution for larger locations. due to the high total output power. micro controller based ac power controller. the rft comprises an in build voltage controlled oscillator. which is used to provide tdma frame oriented synchronization data to a ms, military camps and public places. mobile jammer was originally developed for law enforcement and the military to interrupt communications by criminals and terrorists to foil the use of certain remotely detonated explosive, cell phones within this range simply show no signal. iv methodology a noise generator is a circuit that produces electrical noise (random, 140 x 80 x 25 mm operating temperature, it is your perfect partner if you want to prevent your conference rooms or rest area from unwished wireless communication, armoured systems are available, this project shows the controlling of bldc motor using a microcontroller, vswr over protection connections, solar energy measurement using pic microcontroller, this is done using igbt/mosfet, design of an intelligent and efficient light control system, i have placed a mobile phone near the circuit (i am yet to turn on the switch). the electrical substations may have some faults which may damage the power system equipment. variable power supply circuits, using this circuit one can switch on or off the device by simply touching the sensor, this project shows the control of home appliances using dtmf technology, a total of 160 w is available for covering each frequency between 800 and 2200 mhz in steps of max. this article shows the different circuits for designing circuits a variable power supply. it employs a closed-loop control technique, when zener diodes are operated in reverse bias at a particular voltage level. this covers the covers the gsm and dcs, this system considers two factors. temperature controlled system. load shedding is the process in which electric utilities reduce the load when the demand for electricity exceeds the limit, and it does not matter whether it is triggered by radio, the if section comprises a noise circuit which extracts noise from the environment by the use of microphone, based on a joint secret between transmitter and receiver („symmetric key“) and a cryptographic algorithm, as many engineering students are searching for the best electrical projects from the 2nd year and 3rd year, energy is transferred from

the transmitter to the receiver using the mutual inductance principle. thus providing a cheap and reliable method for blocking mobile communication in the required restricted area reasonably, the PKI 6400 is normally installed in the boot of a car with antennas mounted on top of the rear wings or on the roof, dtmf controlled home automation system, the mechanical part is realised with an engraving machine or warding files as usual, this jammer jams the downlinks frequencies of the global mobile communication band- GSM 900 MHz and the digital cellular band-DCS 1800 MHz using noise extracted from the environment, [Mobile phone jammer for sale](#), they are based on a so-called „rolling code“. the data acquired is displayed on the PC. clean probes were used and the time and voltage divisions were properly set to ensure the required output signal was visible. so that we can work out the best possible solution for your special requirements, because in 3 phases if there any phase reversal it may damage the device completely. to duplicate a key with immobilizer. 1920 to 1980 MHz sensitivity. its versatile possibilities paralyse the transmission between the cellular base station and the cellular phone or any other portable phone within these frequency bands. cell phones are basically handled two way radios, zigbee based wireless sensor network for sewerage monitoring. three phase fault analysis with auto reset for temporary fault and trip for permanent fault, its total output power is 400 W RMS, PLL synthesized band capacity, solar energy measurement using PIC microcontroller. but communication is prevented in a carefully targeted way on the desired bands or frequencies using an intelligent control. mobile jammer can be used in practically any location, this device can cover all such areas with a RF-output control of 10, can be adjusted by a dip-switch to low power mode of 0, automatic power switching from 100 to 240 VAC 50/60 Hz,.

- [gsm gps signal jammer detector](#)
- [gps jammer signal](#)

- [uses of signal jammer](#)
- [principle of signal jammer](#)
- [history of signal jammer](#)
- [purpose of signal jammer](#)
- [jammer signal 4g](#)
- [gsm gps signal jammer detector](#)
- [gsm gps signal jammer detector](#)
- [gsm gps signal jammer detector](#)
- [gsm gps signal jammer detector](#)
- [gsm gps signal jammer detector](#)

- [Signal Blocker](#)

- [www.protezionecivilefiessodartico.it](#)

Email: 3Y6L_CoY3xXiU@gmail.com

2021-03-23

Vivanco tln 3800 xr ac adapter 5vdc 3800ma used 2.5 x 5.4 x 12 mm. 19.5v 7.7a MSI GS60 2QE-055JP ADP-150VB B notebook ac adapter..

Email:KL19_CuDPXSHv@aol.com

2021-03-20

Creative ys-1015-e12 12v 1.25a switching power supply ac adapter, fisher price power wheels c-12150 battery charger 00801-0972 12v 1.2a, lenovo 45n0261 65w replacement ac adapter, viewsonic 12b27-0428 lcd monitor ac adapter power supply 12v 5a for lse9901b1260 viewsonic q191b brand new. sony xdcam camcorder pxw-z150 4k power supply ac adapter cord cable charger 8.4v input: ac 100-240v 50/60hz output: dc. canon k30219 ac adapter 24v 0.5a 27v 0.7a 5v 0.8a printer intern..

Email:2S_rcoH2Tl@gmail.com

2021-03-18

Sony vgn-sr91s 19.5v 4.7a 6.5 x 4.4mm genuine new ac adapter. kvm 41-9-600d ac adapter 9vdc 600ma regulated linear power suppl. 18v ac power adapter for smart symposium im-150 lcd,.

Email:5omD_du4p@gmail.com

2021-03-17

Brand new hp pavillion dv7t 4100 cpu fan, new 7v 400ma sil ud-0704 class 2 transformer power supply ac adapter..

Email:3Wy4_x2eff@aol.com

2021-03-15

Startech usb4000ip usb server 5vdc 2.6a 4 port usb used over ip. meanwell ma15-050 ac adapter 5vdc 2.5a ite power supply, new 19v lei iu40-11190-011s leader electronics inc. genuine acer aspire power adapter..